



## Features

- \*All aluminum fan-less chassis design
- \*Supports Intel® Elkhart Lake J6412, N6210, and X6202RE
- \*Supports wifi/BT/4G/NB-IOT/Zigbee and so on Multiple wireless communication methods
- \*Supports 12-24V wide voltage input



## Specifications

Platform	CPU	Intel® Elkhart Lake J6412/N6210/X6202RE
	Chipset	/
Memory	Type	DDR4 3200MT/s
	Slot	1X 260 pin So-DIMM
	Capacity	Max 16G
Network	Port	2X RJ45 Ports
	Controller	2X Intel i210-AT
Display	Graphic	UHD
	DP	1X DP port, Maximum resolution 4096x2160@ 60Hz
	HDMI	1X HDMI port, Maximum resolution 4096x2160@ 60Hz
	Mode	Independent two diaplays
Internal	SATA	1X SATA3.0, 1*4pin SATA PWR
	SSD	1X Mini-PCIE port, Support Msata
	4G	1X Mini-PCIE ,1X SIM Card slot
	wifi	1XM.2, support wifi/BT
	NB-IOT	1X TTL,support NB-IOT
	Zigbee	1X TTL,support Zigbee
	GPIO	4 road
IO	Power Button	1X
	DC JACK	1X 12V-24V
	COM	2X standard RS232 DB9 ports
	USB	2X USB3.0 ports, 2XUSB2.0 ports
	LAN	2X RJ45 10/100/1000M ports
	DP	1X 1X standard HDMI port
	HDMI	1X standard HDMI port
Power	Power Input	12V-24V DC Power Input
Physical parameters	Demision	128*152*37mm
	Temperature	Working Temperature: -15-50℃; Storage Temperature: -40-70℃
	Humidity	5%-95%, No-Condensation
OS	OS	Windows10/Linux